

PMY104

SCISSOR LIFT

STANDARD FEATURES

Performance

- Easy Onboard Calibration®
- Drive speed proportional to height
- Drive at height
- Speed / Torque Drive Selection
- Front Wheel Drive
- Drive speed proportional to height
- 20% Gradability
- Drive Traction Control System
- Proportional Joystick Controller
- Digital Control Panel
- Customizable Descend Speed
- Foldable Guardrails
- Rotating Beacon on Base
- Non marking Grey Tires
- Horn
- Self Lubricating Bearings
- Hour Meter
- Orange - White Paint
- Forklift Holes

Safety

- TS-EN 280 + A1 / CE Conformity
- Pothole Protection Outriggers
- Emergency Stop Buttons on Control Panels
- Tilt Sensor
- High Pressure Relief Valve
- Brake Release Valve
- Descend Buzzer
- Pressure Holding and Interlocking Valves against Hose Blasts
- Emergency Descend Hand Valve

OPTIONAL FEATURES

- Diesel Engine
- Wireless Remote Controller
- Hydraulic Basket Extension
- Basket Air Outlet
- 110V / 220V / 380V Socket in Basket
- Anemometer on Basket
- Basket Toolbox
- Heavy Duty Solid Rubber Tires
- Additional Lighting
- Custom Paint Color



TECHNICAL DATA		PMY 104
Operating Height		10 m
Platform Height		8 m
Basket Capacity (kg)		300 kg
Basket Dimensions		1100 x 2275 x 1100 mm
(C) Full Height		2350 mm
(A) Height Guardrails Folded		1620 mm
(B) Length		2510 mm
(F) Width		1150 mm
(D) Basket Extension		0,9 m
Basket Extension Capacity		120 kg / 1 Person
Control System		Electronic Proportional Joystick
Weight		2400 kg
Batteries		245Ah/24V DC (6Vx4)
Battery Charger		24V 40Amp/h
Drive System		Hydromotor
Drive Speed (Min/Max)		2km/h-4km/h

