

# PTCR183

TRAILER MOUNTED TELESCOPIC PLATFORMS

## STANDARD FEATURES

### Performance

- 70000V Insulated Fiberglass Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Buzzer
- Basket and Turret Control Panels
- Rotating Beacon on Turret
- Manual Outriggers
- All-terrain Outrigger Swivels
- Height Adjustable Front Wheel

### Safety

- TS-EN 280 + A1 / CE Conformity
- Simultaneous Braking System with Stop Lights
- Hand Brake
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against hose blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump

## OPTIONAL FEATURES

- Fly Boom\*
- Fly Boom Rotation (180° Horizontal)
- External Drive System
- Hydraulic Outriggers
- Automatic One-button Platform Leveling
- Diesel Engine
- 220V AC Motor
- 24V DC Motor (245Ah Battery)
- Tilt Sensor
- Continuous Turret Rotation
- Basket Load Cell
- Basket Rotation
- 110V/220V/380V Socket in Basket
- Aluminium Basket
- Extra Basket Capacity
- Toolbox in Basket
- Emergency Descend DC Powerpack
- Custom Paint Color
- Additional Lighting
- Hydro mechanical Control System
- Wireless Remote Joystick Controller



Technical Data	PTCR 183
Operating Height	18 m
Platform Height	16 m
Lateral Outreach	11 m
Turret Rotation	350°
Basket Capacity (kg)	200 kg
Basket Dimensions	750x1000x1100 mm
Ⓒ Stowed Height	2925 mm
Ⓐ Stowed Length	7000 mm
Ⓑ Stowed Width	2200 mm
Width Outriggers Extended	4400 mm
Control System	Electronic Proportional Joystick
Weight	3250 kg
Power	220V / 380V AC

