

# PT122

TRUCK MOUNTED TELESCOPIC PLATFORMS

## STANDARD FEATURES

### Performance

- 70000V Insulated Fiberglass Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Buzzer
- Basket and Turret Control Panels
- Rotating beacon on Turret
- All-terrain Outrigger Swivels
- Non-slip Body
- Toolbox (2 pieces)

### Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against Hose Blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump

## OPTIONAL FEATURES

- Simultaneous Commands Execution (Full proportional)
- Automatic One-button Platform Leveling
- Fly Boom\*
- Fly Boom Rotation (180° Horizontal)
- Tilt Sensor
- Basket Load Cell
- Extra Basket Capacity
- Basket Rotation
- Anemometer on Basket
- 110V/220V/380V Socket in Basket
- Aluminium Basket
- Steel Basket
- Toolbox in Basket
- Base-Basket Radio Communication
- Continuous Turret Rotation
- Operator Seat
- Operator Cabin
- Hydro mechanical Control System
- Wireless Remote Joystick Controller
- Emergency Descend DC Powerpack
- External AC Powerpack
- Special Paint Color
- Additional Lighting
- Nonslip Aluminium Body
- Additional Toolboxes (+2)



TECHNICAL DATA	PT 122
Operating Height	12 m
Platform Height	10 m
Lateral Outreach	6 m
Turret Rotation	270°
Basket Capacity (kg)	200 kg
Basket Dimensions	750x1000x1100 mm
Stowed Height	2950 mm
Stowed Length	4000 mm
Stowed Width	2050 mm
Width Outriggers Extended	2510 mm
Control System	Electronic Proportional Joystick
Weight	1625 kg

